

LONGSEAL®

LONGSTIK

Double Sided Adhesive Tape

DESCRIPTION

LONGSTIK is a composite laminate, manufactured as a "sandwich" of self-adhesive modified bitumen adhesive between two layers of silicon coated release paper, which are removed as application progresses.

LONGSTIK double-sided adhesive tape is supplied in rolls for use as an adhesive tape to secure LONGSEAL PROTECTION BOARD during the application of LONGSEAL Self Adhesive Waterproof Membranes.

LONGSTIK can also be used as a joining tape in conjunction with damp proof course systems.

STANDARD PRODUCT DETAILS

Thickness:	1.5mm
Width:	50, 75, 100, 150, and 225mm
Length:	15m

APPLICATION

Remove approximately 50cm of the release film. Lay tacky side on one face of the board and press adhesive into place. Continue to remove the release layer pressing firmly. Remove the second release film and press the board firmly into position.

STORAGE GUIDELINES

The tape should be stored in dry, well-ventilated buildings, out of direct sunlight or other major sources of heat. Stock should be rotated on a first in/first out basis.

HEALTH & SAFETY

Material Safety data sheets are available on request.

CHASE PROTECTIVE COATINGS LIMITED
Tel. 0044 (0)1797 223561, Fax 0044 (0)1797 224530
Email: info@chaseprotectivecoatings.com