

LONGWRAP®

LD MASTIC

DESCRIPTION

LD MASTIC is a blend of petrolatum, inert fillers and expanded polystyrene beads. The product is non-setting and non-hardening.

AREAS OF USE

LD MASTIC should be used as a lightweight profiling mastic for moulding around irregular shapes and profiles such as valves, general industrial fittings and joints, prior to overwrapping.

BENEFITS

- ▲ Easy to apply
- ▲ Resistant to dilute Mineral Acids, Alkalis and Salts
- ▲ Non Cracking and Non Absorbent to Moisture

PRODUCT DETAILS

PROPERTY	UNIT	TROPICAL	TEMPERATE
Density	g/ml	0.7 - 1.0	0.7 - 0.8
Filling Capacity	L/kg	1.33	1.33
Temperature Range: Application In Service	°C °C	+5 to +45 +5 to +65	+5 to +35 +5 to +55
Packing Each carton holds 6 slabs	145mm x 50mm x 500mm (approx) approx weight per slab 2.5kg		

APPLICATION

Surfaces should be clean and free from contamination before moulding by hand around the surface to be protected. Ensure container is properly resealed after use.

SURFACE PREPARATION

The substrate should be as clean as possible. Remove all loose matter, dirt and mill scale before application.

STORAGE

LD MASTIC should be stored in their original format until required for use. Store in dry, cool, well-ventilated conditions out of direct sunlight and other major sources of heat. The temperature should not exceed 35°C. Stock should be rotated on the first in/first out basis.

HEALTH & SAFETY

Material Safety Data Sheets giving full information are available

W
W
W
•
L
O
N
G
P
R
O
D
U
C
T
S
•
C
O
•
U
K

CHASE PROTECTIVE COATINGS LIMITED
Tel. 0044 (0)1797 223561, Fax 0044 (0)1797 224530
Email: info@chaseprotectivecoatings.com