

# MAFLOWRAP®

## MOULDING COMPOUND 1190

W  
W  
W  
•  
L  
O  
N  
G  
P  
R  
O  
D  
U  
C  
T  
S  
•  
C  
O  
•  
U  
K

### DESCRIPTION

MC 1190 is a specially formulated flexible and non-hardening compound. It is clean and easy to use by hand.

### USES

MC 1190 should be used as a profiling compound to mould around irregular shapes and profiles such as valves, general industrial fittings, and joints, to give a smooth profile prior to overwrapping with MAFLOWRAP tapes.

### BENEFITS

- ▲ Clean and easy to apply
- ▲ Resistant to dilute mineral acids, alkalis and salts
- ▲ Non cracking and non setting
- ▲ Totally inert composition, non-hazardous

### PRODUCT DETAILS

<b>Composition</b>	Inert inorganic fillers in synthetic saturated hydrocarbon polymer base
<b>Adhesion</b>	Excellent on clean, dry surface
<b>Shrinkage</b>	Nil
<b>Temperature Range</b>	
Storage °C	up to +35
Application °C	+5 to +50
In Service °C	up to +75
<b>Packing</b>	25 kg packs

### APPLICATION

The substrate should be clean and dry. Ensure container is properly resealed after use.

### STORAGE

MC 1190 should be stored in the original container until required for use. Store in dry, cool, well-ventilated buildings out of direct sunlight and other major sources of heat. Storage conditions should be adjusted before application to bring the temperature of the material to within the relevant specified application range. Stock should be rotated on the first in/first out basis.

### HEALTH & SAFETY

Material Safety Data Sheets giving full information are available.

**CHASE PROTECTIVE COATINGS LIMITED**  
Tel. 0044 (0)1797 223561, Fax 0044 (0)1797 224530  
Email: [info@chaseprotectivecoatings.com](mailto:info@chaseprotectivecoatings.com)