

# MAFLOWRAP®

## PRIMER B400

### DESCRIPTION

PRIMER B400 is a high solids priming solution designed to be used with MAFLOWRAP tapes. This Primer is manufactured from bituminous solids with a fast drying hydrocarbon solvent.

PRIMER B400 acts as the primary anti-corrosion layer. The Primer enhances the rapid formation of a strong adhesive bond between the tape layer and the primed substrate. In the case of freshly prepared metal surfaces immediate application of this Primer prevents flash rusting.

PRIMER B400 plays an important part in the corrosion protection system by providing the correct conditions for wrapping.

### APPLICATION

PRIMER B400 can be applied by brush, roller or spray. Ensure containers are properly resealed after use. When dry, MAFLOWRAP tapes can be applied on to the primed surface.

### PRODUCT DETAIL

TECHNICAL PROPERTY	UNIT	TYPICAL RESULTS
Colour		Black
Flash Point	°C	23
Solids	%	57
Coverage	m <sup>2</sup> /l	6 - 10

### PACKAGING

PRIMER B400 is supplied in 5, 25 and 200 litre units.

### STORAGE

PRIMER B400 should be stored in the original sealed containers until required for use. Store in dry, cool, well-ventilated buildings out of direct sunlight and other major sources of heat. Stock should be rotated on the first in/first out basis.

Primers give off a flammable vapour and should be stored in accordance with local hazard requirements.

### HEALTH & SAFETY

Material Safety Data Sheets giving full information are available.

**CHASE PROTECTIVE COATINGS LIMITED**

**Tel. 0044 (0)1797 223561, Fax 0044 (0)1797 224530**

**Email: [info@chaseprotectivecoatings.com](mailto:info@chaseprotectivecoatings.com)**

# MAFLOWRAP®

## MOULDING COMPOUND 1190

W  
W  
W  
•  
L  
O  
N  
G  
P  
R  
O  
D  
U  
C  
T  
S  
•  
C  
O  
•  
U  
K

### DESCRIPTION

MC 1190 is a specially formulated flexible and non-hardening compound. It is clean and easy to use by hand.

### USES

MC 1190 should be used as a profiling compound to mould around irregular shapes and profiles such as valves, general industrial fittings, and joints, to give a smooth profile prior to overwrapping with MAFLOWRAP tapes.

### BENEFITS

- ▲ Clean and easy to apply
- ▲ Resistant to dilute mineral acids, alkalis and salts
- ▲ Non cracking and non setting
- ▲ Totally inert composition, non-hazardous

### PRODUCT DETAILS

<b>Composition</b>	Inert inorganic fillers in synthetic saturated hydrocarbon polymer base
<b>Adhesion</b>	Excellent on clean, dry surface
<b>Shrinkage</b>	Nil
<b>Temperature Range</b>	
Storage °C	up to +35
Application °C	+5 to +50
In Service °C	up to +75
<b>Packing</b>	25 kg packs

### APPLICATION

The substrate should be clean and dry. Ensure container is properly resealed after use.

### STORAGE

MC 1190 should be stored in the original container until required for use. Store in dry, cool, well-ventilated buildings out of direct sunlight and other major sources of heat. Storage conditions should be adjusted before application to bring the temperature of the material to within the relevant specified application range. Stock should be rotated on the first in/first out basis.

### HEALTH & SAFETY

Material Safety Data Sheets giving full information are available.

**CHASE PROTECTIVE COATINGS LIMITED**  
Tel. 0044 (0)1797 223561, Fax 0044 (0)1797 224530  
Email: [info@chaseprotectivecoatings.com](mailto:info@chaseprotectivecoatings.com)