

Serviwrap[®] Moulding Putty

Anti-corrosion Pipewrap

Use

Complementing the range of Serviwrap Anti-corrosion Pipewraps, Serviwrap Moulding Putty is used to mould around pipe fittings such as flanges, valves, spigot and socket type joints, and bolted couplings, to provide a more suitable profile for wrapping with Serviwrap tape.

Easy and clean to handle

Serviwrap Moulding Putty is designed for hand-moulding and it is fast and simple to use.

Climatic Zone

Temperate and Tropical

Good Adhesion

Serviwrap Moulding Putty should be applied over Serviwrap Primer AB and exhibits good adhesion remaining in place without slumping.

Supply

Packed in heavy duty plastic drums, 22.5 kg plastic drums, or in 25 kg strips packed in cartons.

Nominal Physical Data

Filling Capacity Approx. 1.90 kg/litre

Colour Natural

Application Instructions

Subject to alteration for specific requirements.

1. Surface to be thoroughly cleaned to remove rust, mill scale, weld spatter, dirt, dust, grease and other deleterious matter.
2. Dry, clean, prepared surface to be primed by brush with one thin continuous coat of SERVIWRAP Primer AB (quick-drying) which must be allowed to dry completely.

3. Pack SERVIWRAP MOULDING PUTTY into crevices around bolts etc, to provide even contour suitable for wrapping.

Material Health and Safety Data

See relevant Material Health and Safety Data Sheet.